

# Door Sales Inc.

Industrial Door Solutions

15252 Stony Creek Way Suite 103  
 Noblesville, IN 46060  
 317-773-9218 fax 317-773-9275  
 www.doorsales.net 800-839-2293

## 1816 / 1814 Fiberglass Mesh Model 10, 50, 150

Strands per square inch: 18 wide 16 Long or 18 wide x 14 Long

Open Percentage 60% or 58%  
 Tear Strength 10 or 14  
 Burst Strength 86 or 155  
 Thread Thickness .013 or .016  
 Colors: Black Standard (Gray Special Order)

## 2020 Fiberglass Mesh Model 12, 52, 152

Strands per square inch 20 wide x 20 long  
 Open Percentage 45%  
 Tear Strength 15  
 Burst Strength 207  
 Thread Thickness .016  
 Colors: Black Standard (Gray Special Order)

## Vinyl Coated Polyester Mesh Model 17, 57, 157

14 color options

Vinyl mesh allow good airflow while keeping most insect classes out.

Shading properties can cut down solar heat gain keeping the interior of the building cooler.

17 x 11 Mesh Size  
 Openness Percentage 35%  
 Tensile Strength 389 warp  
 Tear Strength 91  
 Thread Thickness .033  
 Mesh weight 11.3  
 Blocking shade scale 2

## Screen Mesh Options

### Model

10, 12, 17

50, 52, 57

150, 152, 157

