

Door Sales Inc.

Industrial Door Solutions

15252 Stony Creek Way Suite 103
Noblesville, IN 46060
317-773-9218 fax 317-773-9275
www.doorsales.net 800-839-2293

900 Track Lift Options

The 900 is a unique sectional type door system that is designed to work in conjunction with existing sectional overhead door type doors. Shown below are the most common track and spring configuration to work with the existing sectional door system. The door is supplied with special outside bottom fixtures and extended door shafts to allow the door cable to work outside the door track.

Highlift or Lift Clearance Track —>

- Typical high lift or lift clearance installation with a diverter switch allows the use of the same lower door track.
- The highlift track is for use in areas where the ceiling height does not allow the use of vertical lift track.
- The spring system can be located in several locations depending on field conditions. The spring can be located above the existing spring, at the back of the door tracks, at a midpoint location above both doors (as shown) or under the existing door between the door tracks. This is driven by field conditions and may require pulleys (not supplied) and adjusting the cable length.
- Highlift track is available in several lift options up to 54" lift clearance, 120" lift clearance and 164" lift clearance.



<— Vertical Lift Track

- Most common installation is a vertical lift track with diverter switch.
- The spring system can be mounted above the existing doors spring system (as shown). It can also be mounted between the existing overhead door and the screen door.
- The door is supplied with special outside bottom fixtures and extended door shafts to allow the door cable to work outside the door track.

Other Track Mounting Systems

- Standard lift track
- Low Headroom Track
- Dual Track
- Rolling Steel Door Attachments